



Sand dynamics on beaches and shorefaces

T. Verwaest, R. Delgado, J. Janssens and J. Reyns








Point of view of coastal protection

1) Protection against superstorms



PRACTICE

Masterplan Kustveiligheid: ±1 million m3 / year (2010...2015...)







Point of view of coastal protection

2) Protection against structural erosion

PRINCIPLE

- Hold the line
- Seaward development
- Managed retreat

PRACTICE

- NL, DK, Sylt (D),...: hold the line
- UK (local cliff erosion): managed retreat (locally)
- B: hold the line => seaward development ? => Vlaamse Baaien study








Complexity

Natural sand dynamics and coastal morphology


- Drivers: waves, tides, grain size distribution, human activities (infrastructure works, dredging, nourishments)
- Spatial scale: kilometers, dunes-beaches-shorefaces-gulliessandbanks
- Time scales: years, decades, storm effects
- ⇒ present insight in coastal sand balans is limited
- ⇒ current models have limited predictive capacities
- ⇒ large needs for integrated research combining modeling with most importantly in-situ measurements / monitoring

Example of longshore sand transport in breaker zone (littoral drift)





topography/bathymetrie
beach - shoreface
Blankenberge - Zeebrugge











The problem





•Tidal range ~4 m







The problem

How to make a first estimation of the net longshore sand transport if....

- -No direct measurements available.
- -Poor performance of available models.







Methodology and tools

Complex problem _____start with simple tools:

- GIS based morphological trend analysis.
- 1D Numerical modelling.







Morphological trends analysis

Tool: ArcGIS

± 15 year topo-bathymetric data (1995-2010)

 Datasets completed by inventory of dredging, disposal and nourishment activities in the study area.

Goals:

- Identification of clear erosion and accretion zones.
- First estimation of net rates in the area.








Results of the trends analysis

Net longshore transport estimation 400000±35000 m³/y










Numerical modelling

Tool: LITPACK – LITDRIFT



Goals:

- Identification of most active area for longshore transport for figures obtained in the trend analysis.
- Calibrate roughness to reproduce empirical value of littoral drift and separate net rate into two bruto rates NE 3,5 ÷ SW 1







Lessons learned

- The "taking a very simple first approach to a complex problem" principle helps to learn about how the problem should be tackled.
- It is possible to have an acceptable first estimation of net (longshore) transport based on morphological trends analysis.
 The method will be useful to compare with results from numerical models.
- It is necessary to further develop combination of different tools and methodologies.
- Estimate of littoral drift for B-coast:
 - NET +- 400.000 m3/year to NE
 - Bruto to NE +- 550.000 m3/year
 - Bruto to SW +- 150.000 m3/year







Current and further work

- Improving of numerical modeling tools for beaches and shorefaces sand dynamics / morphology / hydraulics :
 - Use of 2D models accounting for cross-shore as well as long-shore effects.
 - Investigating model abilities to account for the presence of structures (e.g. groins).
 - Calibration/validation with high quality data.
- Improving the trends analysis method:
 - Assess uncertainty on trend results from measurement inaccuracies (topo/bathy).
 - Using more datasets and including more accurate figures about dredging, nourishment etc.
- Intensive in situ measuring and monitoring on beaches and shorefaces
 - smaller scale to better understand processes
 - larger scale to better understand the system

