

## Wave overtopping discharge over a dike for variable water level

Streicher Maximilian<sup>1</sup>, Pepi Yuri<sup>2</sup>, Franco Leopoldo<sup>3</sup>, Bellotti Giorgio<sup>3</sup>, Hughes Steven<sup>4</sup> and Troch Peter<sup>1</sup>

<sup>1</sup> Department of Civil Engineering, Ghent University, Technologiepark 60, B-9052 Zwijnaarde, Ghent, Belgium

E-mail: maximilian.streicher@ugent.be

<sup>2</sup> Flanders Marine Institute (VLIZ), Jacobsenstraat 1, 8400 Oostende, Belgium

<sup>3</sup> Department of Engineering, University of Roma TRE, Via Vito Volterra 62, 00146 Rome, Italy

<sup>4</sup> Emeritus Colorado State University, Fort Collins, USA

### Introduction

The still water level (SWL) during a storm is always dynamic (storm surge). The variability of the water level can be schematized as a time-varying hydrograph of a certain duration. The average wave overtopping discharge  $q$  is a function of the ratio between the freeboard  $R_c$  (the structure crest elevation above SWL) and the significant wave height  $H_{m0}$ . Since the variation during a storm of the SWL changes the freeboard  $R_c$ , the wave overtopping discharge is variable. Typically, in the laboratory the wave overtopping on coastal defense structures is investigated for a constant water level (CWL) and a pre-determined structural exposure time frame. This exposure time frame is often representative for the storm surge peak or for a statistically representative number of individual waves (e.g. 1000 waves), not considering any variable water level (VWL). Prediction of the average wave overtopping discharge of coastal structures is derived from empirical formulae, e.g. EurOtop, 2018 for the average overtopping discharge over a dike slope and CWL. For the case of wave overtopping in VWL conditions, no validated prediction formulae exist (Kerpen *et al.* 2020) and the prediction is rather based on safe assumptions and engineering judgement.

### Aim and methodology of the research

This research investigated the influence of a VWL on the prediction of the average wave overtopping discharge  $q$ . Physical model tests were conducted in the wave flume at Ghent University for a situation with VWL and a prediction method including VWL effects was derived. The wave flume at Ghent University is 30 m long, 1.0 m wide and 1.2 m high. The model consists of a dike (smooth impermeable slope) with a slope angle  $\cot(\alpha) = 2$ . A total of 139 tests were performed, both under CWL and VWL conditions. Different storm durations (from 15 min to 120 min) and storm surges (0.15, 0.10, 0.05, 0.025 m) were tested in model scale (Froude length scale 1-to-20). By combining tests with different durations, the data-set was synthetically enlarged, resulting in 3873 tests used for the analysis.

### Analysis

Firstly, calibration tests to evaluate the performance of the active wave absorption system in VWL situations, were analyzed. Secondly, the experimental data were processed to derive the incident and reflected wave conditions. Thirdly, the CWL and VWL results in terms of wave overtopping, both average discharge  $q$  and individual volumes  $V_i$ , were calculated.

The prediction performance of EurOtop 2018 formulae was evaluated, and their limitations were identified. At the conference the results from this experimental campaign will be presented, to demonstrate the influence of the VWL on the prediction of average overtopping discharge  $q$ , not previously investigated yet.

### References

- Kerpen *et al.* (2020): Effect of variations in water level and wave steepness on the robustness of wave overtopping estimation., *Journal of Marine Science and Engineering*, Volume 8, pp 63
- Van der Meer *et al.* (2018): EurOtop, Manual on wave overtopping of sea defences and related Structures. An overtopping manual largely based on European research, but for worldwide application. [www.overtopping-manual.com](http://www.overtopping-manual.com)

### Keywords

Overtopping Discharge; Variable Water Level; Storm Surge; Impermeable Sloping Structure; Experimental Model Tests