

De Paepe Willems Award 2017 – Second Place

BOW AND STERN SINKAGE COEFFICIENTS FOR CARGO SHIPS IN SHALLOW OPEN WATER

JEONG HUN HA

is a Ph.D. candidate at the Centre for Marine Science and Technology (CMST) at Curtin University, Australia.

His Ph.D. thesis is about ship under-keel clearance in port approach channels. His background is as a Korean civil engineer in the design of port and coastal structures.



TIM GOURLAY

is Director of Perth Hydro Pty Ltd and supervising Jeong Hun Ha's Ph.D. thesis.

He undertakes research and consulting work in ship under-keel clearance for ports in Australia and internationally. He is the author of ShallowFlow and SlenderFlow software, and has conducted full-scale ship motion measurements on 60 cargo ship transits through navigation channels.



Keywords: sinkage, approach channel, shallow water, ship hulls, ship under-keel clearance

Mots clés : enfoncement, chenal d'approche, coque de bateaux, clair sous quille

1 Introduction

When a ship is under way in shallow calm water, it experiences a downward sinkage and dynamic trim change, which are collectively called 'squat'. This is a Bernoulli effect, whereby the free surface drops as water is accelerated along the sides of the ship. The ship then sinks hydrostatically into its own wave trough, bringing it closer to the seabed. Squat has been a significant contributing factor in several grounding incidents [Nautical Institute, 2015].

The recent PIANC guidelines for harbour approach channels [PIANC, 2014] contain information on suitable squat allowances for different types of ships and channels. The methods are semi-empirical, and several [Hooft, 1974 ; Huuska, 1976 ; ICORELS, 1980 ; Millward, 1992] are based on the slender-body analysis of Tuck (1966) for ships in shallow open water. According to that theory, the midship, bow, and stern sinkage may be written

$$S_{mid} = C_{s_{mid}} \frac{\nabla}{L_{PP}^2} \frac{F_h^2}{\sqrt{1-F_h^2}} \quad (1)$$

$$S_{bow} = C_{s_{bow}} \frac{\nabla}{L_{PP}^2} \frac{F_h^2}{\sqrt{1-F_h^2}} \quad (2)$$

$$S_{stern} = C_{s_stern} \frac{\nabla}{L_{PP}^2} \frac{F_h^2}{\sqrt{1 - F_h^2}} \quad (3)$$

where F_h is the depth-based Froude number:

$$F_h = \frac{U}{\sqrt{gh}} \quad (4)$$

Here U is the ship speed, h is the water depth, and g is the gravitational acceleration. ∇ is the ship's displaced volume and L_{PP} is the ship's length between perpendiculars.

In open water, the sinkage coefficients C_{s_mid} , C_{s_bow} , and C_{s_stern} are predicted to be constant for each ship, irrespective of the ship speed or water depth. The sinkage coefficients should also be independent of scale. For a rigid hull, as is normally assumed,

$$C_{s_mid} = \frac{(C_{s_bow} + C_{s_stern})}{2} \quad (5)$$

Equations (1), (2), and (3) suggest a semi-empirical method to predict ship sinkage. That is, perform model testing to calculate the sinkage coefficients experimentally, then apply these same empirical coefficients to predict sinkage for full-scale ships.

A problem with the semi-empirical approach is that model tests are necessarily performed in a finite-width tank, for which the sinkage coefficients are not constant, but also depend on the tank width, water depth, and ship speed. The linear finite-width theory of Tuck (1967) suggests that sinkage will increase as the channel width decreases. In addition, nonlinear effects become increasingly important as the channel width decreases. These effects mean that sinkage coefficients are found not to be constant for each ship. As an example, the MEGA-JUMBO container ship model [Uliczka et al., 2004] was found to have midship sinkage coefficients ranging from 1.40 - 1.76 in the widest channel configuration tested, and 2.02 - 2.20 in the narrowest channel configuration tested [Gourlay et al., 2015a].

Why not use smaller-scale models in shallow-water model tests, to minimize the tank width effect? This approach was taken by Graff et al. (1964) who used 6m models for deep-water tests and 3-m models for shallow-water tests. Unfortunately, using small models increases the viscous scale effect, which is important for dynamic trim. Therefore, choosing the model scale is a compromise between minimising tank width effect and minimising scale effect. Needless to say, wide tanks, such as the 10-m wide Duisburg tank, are highly sought-after for shallow-water tests.

Some authors have tried to capture the dependence on channel width through empirical corrections to the sinkage coefficients [PIANC, 2014]. While this might work well for the ship models and channels used to develop the correction, the physics might not be adequately captured to be able to apply these methods to a wide range of ships.

We would recommend that complete numerical simulations be performed for ships in channels. For moderate-width channels, the linear slender-body theory of Tuck (1967) may be used; for narrow channels, the nonlinear Rankine-source method [von Graefe, 2014] may be used; for very narrow channels, the nonlinear hydraulic theory of Gourlay (1999) may be used. RANS methods are also becoming increasingly common for modelling ship sinkage and trim, especially in confined waterways [Mucha et al., 2014].

Here, we concentrate on waterways with minimal transverse restriction, such as open waterways or dredged channels, which are common for port approach channels on the Australian continental shelf. For these types of waterways, we develop sinkage coefficients that may be used for under-keel clearance management. The coefficients are calculated using the slender-body theory of Tuck (1966) for open water, Tuck (1967) for canals, and Beck et al. (1975) for dredged channels. The methods are implemented in the computer code 'ShallowFlow' developed at the Centre for Marine Science and Technology, Curtin University [Gourlay, 2014]. For wide channels, slender-body theory has been shown

to give good results for container ships at model scale [Gourlay et al., 2015a], container ships at full scale [Gourlay, 2008a], bulk carriers and tankers at model scale [Gourlay, 2006 ; Gourlay et al., 2016], and bulk carriers and tankers at full scale [Gourlay, 2008b ; Ha et al., 2016].

2 Cargo Ship Types and Representative Ship Models

While line plans for merchant cargo ships are generally confidential, many ship hull forms for research objectives have been developed over the years. Here, 12 published representative ship models have been chosen for analysis. These fall into the categories of container ships, bulk carriers, oil tankers, or membrane LNG carriers. Oil tankers and bulk carriers are grouped together due to parallels in hull shape between them.

Ships carrying different types of cargo have evolved to have different hull shapes. Shipping containers are fairly low density and need to be transported quickly, so container ships tend to have low block coefficient, to maximize waterplane area for their displacement and give an efficient hull shape. Bulk carriers and tankers have high-density cargo with less requirement for speed, so the hull shapes tend to have high block coefficient, to maximise deadweight capacity at the expense of hull efficiency. Membrane LNG carriers are generally in between container ships and tankers in terms of hull shape and block coefficient, but have shallower draught because of their low-density cargo.

In this paper, we shall be focussing only on container ships, bulk carriers, oil tankers, and membrane LNG carriers, which are the hull types we shall be analysing. Therefore, these results are not directly applicable to other cargo ship types, such as Ro-Ro vessels, car carriers, livestock carriers, Moss LNG carriers, LPG carriers, and warships.

The container ships modelled are:

- 'Duisburg Test Case' ('DTC', 355m L_{PP}), designed by the University of Duisburg-Essen, Germany in 2012, representative of a 14,000 TEU Post-Panamax container ship [El Moctar et al., 2012]
- 'KRISO Container Ship' ('KCS', 230m L_{PP}), designed by Korean Research Institute Ships and Ocean Engineering (KRISO) in 1997, representative of a 3,600 TEU Panamax container ship [Lee et al., 2003]
- 'JUMBO' (320m L_{PP}), designed by SVA Potsdam, Germany in 1995, representative of a 5,500 TEU Post-Panamax container ship [Uliczka et al., 2004]
- 'MEGA-JUMBO' (360m L_{PP}), designed by VWS Berlin, Germany in 2001, the design ship for the Jade Weser port in Germany, representative of a 12,000 TEU Post-Panamax container ship [Uliczka et al., 2004]
- 'FHR Ship D' (291.13m L_{PP}), designed by Flanders Hydraulics Research and Ghent University, Belgium in 1996-2000, representative of a Post-Panamax container ship [Gourlay et al., 2015b ; Vantorre and Journée, 2003]
- 'FHR Ship F' (190m L_{PP}), designed by Flanders Hydraulics Research and Ghent University, Belgium in 1996-2000, representative of a Panamax container ship [Gourlay et al., 2015b ; Vantorre and Journée, 2003]

The oil tankers modelled are:

- 'KRISO Very Large Crude Oil Carrier' ('KVLCC', 320m L_{PP}), designed by Korean Research Institute Ships and Ocean Engineering (KRISO) in 1997, representative of a 300,000 DWT oil tanker [Larsson et al., 2003 ; Van et al., 1998]
- 'KRISO Very Large Crude Oil Carrier 2' ('KVLCC2', 320m L_{PP}), designed by Korean Research Institute Ships and Ocean Engineering (KRISO) in 1997, representative of a 300,000 DWT oil tanker, the second version of the KVLCC with more U-shaped stern frame-lines [Larsson et al., 2003 ; Van et al., 1998]

The bulk carriers modelled are:

- 'Japan 1704B standard series' (6m model L_{PP}), designed by National Maritime Research Institute (NMRI, former Ship Research Institute of Japan), representative of a Panamax bulk carrier [Yokoo, 1966]

- 'Japan Bulk Carrier' ('JBC', 280m L_{PP}), designed by National Maritime Research Institute (NMRI, former Ship Research Institute of Japan), Yokohama National University, and Ship Building Research Centre of Japan, representative of a Post-Panamax bulk carrier [NMRI, 2015]
- 'FHR Ship G' (180m L_{PP}), designed by Flanders Hydraulics Research and Ghent University, Belgium in 1996-2000, representative of a Panamax bulk carrier [Gourlay et al., 2015b ; Vantorre and Journée, 2003]

The membrane LNG carrier modelled is:

- 'KRISO Liquefied Natural Gas Carrier' ('KLNG', 266m L_{PP}), designed by Korean Research Institute Ships and Ocean Engineering (KRISO) in 2003, representative of a 138,000 m³ membrane LNG carrier [Van et al., 2003, 2006]

In this paper, hull shapes of the above 12 ships have been developed from supplied IGES files and the published lines plans using Rhino, AutoCAD, and Maxsurf Modeler. Calculated details of the modelled vessels are given in Table 1 and Table 2. Note that some of the particulars have been calculated from the modelled vessels and are approximate. Longitudinal centre of buoyancy (LCB) and longitudinal centre of floatation (LCF) are given as % of L_{PP} forward of aft perpendicular (AP). Block coefficient is the ratio of displacement to (L_{PP}.Beam.Draught). Dimensions of the Japan 1704B are at model scale, as no full-scale dimensions were specified.

Particulars	Container ships					
	DTC	KCS	JUMBO	MEGA-JUMBO	FHR Ship D	FHR Ship F
L _{PP} (m)	355.00	230.00	320.00	360.00	291.13	190.00
Beam (m)	51.00	32.20	40.00	55.00	40.25	32.00
Draught (m)	14.50	10.80	14.50	16.00	15.00	11.60
Block coefficient (-)	0.660	0.650	0.721	0.681	0.604	0.600
Displacement (m ³)	173,337	52,013	133,901	215,775	106,226	42,338
Max. section area (m ²)	730.02	342.42	564.22	867.53	593.13	365.02
LCB (%)	49.04	48.52	49.30	49.97	47.05	47.74
LCF (%)	45.38	44.33	45.84	49.12	44.54	45.43

Table 1: Details of the container ships used for numerical calculations

Particulars	Oil tankers		Bulk carriers			LNG Carrier
	KVLCC1	KVLCC2	Japan 1704B	JBC	FHR Ship G	KLNG
L _{PP} (m)	320.00	320.00	6.00	280.00	180.00	266.00
Beam (m)	58.00	58.00	0.923	45.00	33.00	42.60
Draught (m)	20.80	20.80	0.334	16.50	11.60	11.30
Block coefficient (-)	0.810	0.810	0.801	0.858	0.839	0.749
Displacement (m ³)	312,738	312,622	1.482	178,370	57,806	95,940
Max. section area (m ²)	1,203.80	1,203.80	0.306	741.11	381.69	473.53
LCB (%)	53.48	53.52	54.93	52.53	53.36	49.97
LCF (%)	49.75	50.02	52.16	49.30	51.09	47.65


Table 2: Details of the oil tankers, bulk carriers, and LNG carrier used for numerical calculations

We can see that there are significant differences in hydrostatic characteristics between the hulls. Block coefficient ranges between 0.60 and 0.72 for the container ships, 0.80 and 0.86 for the oil tankers/bulk carriers, and 0.75 for the LNG carrier. Longitudinal centre of buoyancy (LCB) ranges from 47.05 % to 49.97 % for the container ships; from 52.53 % to 54.93 % for the oil tankers/bulk carriers; and 49.97 % for the LNG carrier. Longitudinal centre of floatation (LCF) is aft of the LCB by on average 2.8 %, 3.0 %, and 2.3 % for the container ships, oil tankers/bulk carriers, and LNG carrier, respectively.

and 2.3 % of L_{PP} for the container ships, oil tankers/bulk carriers, and LNG carrier respectively. By looking at these, we see that each ship hull exhibits typical features of their ship type. Slower full-form ships such as tankers or bulk carriers, for example, tend to have their LCB well forward of amidships, while fine-form ships such as container ships and LNG carriers have their LCB slightly aft of amidships [PIANC, 2014].

Comparative body plans of the ships are shown in **Error! Reference source not found.-**

Fig 4. These body plans illustrate 50 evenly-spaced stations from the transom to the front of the bulb. The body plan of the Japan 1704B has a different scale to the others.






Figure 1: Body plans and rendered views of the container ships




Figure 2: Body plans and rendered views of the oil tankers









Figure 3: Body plans and rendered views of the bulk carriers





Figure 4: Body plan and rendered views of the LNG carrier

We can see that there are significant differences in hull shape between the different ship types. Distinctive characteristics in hull shape for the container ships are: a pronounced bow bulb; a wide and nearly flat-bottomed transom stern; and aft sections that are close to horizontal at the waterline. For the oil tankers and bulk carriers, the forward sections are almost vertical, and aft sections are not far from vertical, at the waterline. The oil tankers and bulk carriers have smaller transoms and sharper bow bulbs than the container ships. The KLNG is generally in between the container ships and the oil tankers with regard to hull shape.

In addition, **Error! Reference source not found.-**

Fig 4 show the bow, stern, profile, bottom, and perspective views of the modelled ships, emphasizing each ship type's features in hull shape. We see that the container ship hulls have streamlined forward and aft sections, whereas the hulls of the oil tankers and bulk carriers are very-block with a long parallel midbody. The KLNG hull has a long parallel midbody and streamlined forward and aft sections.

3 Open-Water Sinkage Coefficients

We shall now calculate open-water sinkage coefficients for all of the hulls using the slender-body theory of Tuck (1966). The theoretical sinkage coefficient for each ship type, as calculated using equation (1), (2), and (3), is shown in Table 3.

Ship Hulls		Draught (m)	Sinkage Coefficient (C_s)			Trim (+, stern down)
			Bow (C_{s_bow})	Midship (C_{s_mid})	Stern (C_{s_stern})	
Container Ships	DTC	13.0	1.460	1.342	1.245	(-)
		14.0	1.590	1.272	1.010	(-)
		14.5	1.647	1.242	0.908	(-)
	KCS	10.0	1.643	1.371	1.144	(-)
		10.8	1.830	1.273	0.806	(-)
	JUMBO	14.5	1.721	1.174	0.633	(-)
	MEGA-JUMBO	16.0	1.260	1.400	1.523	(+)
	FHR Ship D	15.0	1.495	1.278	1.065	(-)
FHR Ship F	11.6	1.409	1.361	1.314	(-)	
Overall		-	1.26 - 1.83	1.17 - 1.40	0.63 - 1.52	
Oil Tankers	KVLCC 1	20.8	2.035	1.198	0.371	(-)
	KVLCC 2	20.8	2.018	1.204	0.400	(-)
Bulk Carriers	Japan 1704B	0.33	1.906	1.277	0.649	(-)
	JBC	16.5	1.946	1.236	0.536	(-)
	FHR Ship G	11.6	1.939	1.255	0.586	(-)
Overall		-	1.90 - 2.03	1.20 - 1.27	0.37 - 0.65	
LNG Carrier	KLNG	11.3	1.611	1.410	1.211	(-)

Table 3: Calculated bow, stern and midship sinkage coefficients for open water

We see that hull shape is critical for these results. The bow sinkage coefficient for the group of the oil tankers and bulk carriers, which ranges between 1.90 and 2.03, on average, is 26 % larger than that of the container ships, and 22 % larger than the LNG carrier's value. The midship sinkage coefficient ranges from 1.17 for the JUMBO of the container ship type through to 1.41 for the KLNG. In considering the difference between C_{s_bow} and C_{s_stern} for the ships, dynamic trim for the container ships is generally quite small, but some trim quite strongly bow-down. Similar results were found in full-scale measurements on 16 container ships in Hong Kong [Gourlay and Klaka, 2007].

Theoretically, the sinkage coefficient in open water is constant for each ship, regardless of the ship speed or water depth, but does depend on hull shape. Therefore, we offer a guideline based on Table 3 for making a choice of the sinkage coefficient corresponding to different ship types. These recommended sinkage coefficients are shown in Table 4.

Ship Types	Sinkage Coefficient (C_s)		
	Bow (C_{s_bow})	Stern (C_{s_stern})	Max (C_{s_max})
Container Ships	1.3 - 1.8	0.6 - 1.5	1.8
Oil Tankers & Bulk Carriers	1.9 - 2.0	0.4 - 0.7	2.0
LNG Carriers	1.6	1.2	1.6

Table 4: Recommended sinkage coefficients with respect to ship types in open water

4 Limitations on Using the Sinkage Coefficients for Different Bathymetries

If we wish to put limitations on using the sinkage coefficients, we can compare how the sinkage coefficient is changing with channel dimensions. We consider three idealised types of approach channel, as defined in PIANC (2014), and shown in Figure 5.




Figure 5: Channel configurations: unrestricted (open-water), restricted (dredged) and canal

Figure 6 illustrates relevant parameters for calculating sinkage coefficients of the ship travelling at 12 knots in the dredged channel. A 4H: 1V slope that is typical of channels dredged through surficial sandy seabeds in Western Australia is applied to both the dredged channel and canal configurations [Gourlay, 2013]. The depth in the channel (including tide) and canal is set for shallow water condition of $h/T = 1.2$ [Jachowski, 2008 ; Vantorre, 2003] with varying trench depth (h_T) for the dredged channel. According to the theory, the channel width is modelled as a step depth change from channel depth (h) to outer water depth (h_o) at half-way along the slope on each side of the channel.




Figure 6: Channel configuration modelled and important parameters

The effect of different bathymetries such as channel width (to the toe of slope) and trench depth (h_T), ranging from h_T/h of 0.1 to 0.5, is shown in Figure 7. The results plotted are the ratio of C_{s_max} to C_s in open water.




Figure 7: Effect of transverse bathymetry on predicted sinkage coefficient

We see in these results that the channel and canal sinkage coefficients are all larger than the open-water value, by an amount that depends on the channel bathymetry. For the most restricted case in the dredged channels ($W / L_{PP} = 0.5$, $h_T / h = 0.5$), the maximum sinkage coefficient for the container ships is on average 19 % larger than in open water, while that for the oil tankers and bulk carriers, and KLNG are on average 13 % and 21 % larger than the open-water value respectively. The difference between ship types is mainly because the transverse restriction increases the midship sinkage, but not the dynamic trim [Gourlay et al., 2015a].

Figure 7 may be used to determine whether a particular ship and channel configuration may be classed as open water, or whether a specific narrow-channel analysis is required. For example, we may say that if the channel sinkage coefficient is within 5 % of the open-water value, it is acceptable to use open-water theory. Table 5 shows this assessment for example port approach channels in Western Australia. Note that the calculations have been done at Lowest Astronomical Tide (LAT).

Port approach channel	Fremantle (Deep Water Channel)	Geraldton	Barrow Island
	Dredged channel (chart AUS112)	Dredged channel (chart AUS81)	Dredged channel (chart AUS66)
Channel width (w)	300 m	180 m	260 m
Dredged depth (h)	16.4 m	14.0 m	13.5 m
Approximate trench depth (h_T)	1.1 m	3.0 m	6.0 m
h_T / h	0.07	0.21	0.44
Example ship	Post-Panamax container ship	Panamax iron ore carrier	KLNG membrane LNG carrier
L_{PP}	260 m	215 m	266 m
w / L_{PP}	1.15	0.84	0.98
Maximum sinkage coefficient – variation from open-water value	~1 %	~3 %	~8 %

Table 5: Variation from open-water conditions, for example ships and channels in Western Australia

Table 5 shows that the Fremantle and Geraldton channels may be classed as open water for predicting ship sinkage and trim, while a specific narrow-channel analysis would be recommended for the Barrow Island channel.

The sinkage coefficient for the canal is considerably higher than that for open-water as presented in Figure 7. However, when the canal width is equal to or greater than three times the L_{PP} , we see that canal effects are minimal, as the Tuck (1967) results are within 5 % of the open water [Tuck, 1966] results.

5 Conclusions

For under-keel clearance management, sinkage coefficients have been developed for use in open waterways or dredged channels. The ships considered here for calculating the sinkage coefficients are of a broad range of ships: the DTC, KCS, JUMBO, MEGA-JUMBO, FHR Ship D, and FHR Ship F for container ships; the KVLCC1 and KVLCC2 for oil tankers; the Japan 1704B, JBC, and FHR Ship G for bulk carriers; and the KLNG for membrane LNG carriers. The following conclusions are drawn from the study:

- The sinkage coefficient in open water varies from ship hull to ship hull, but distinguishing characteristics depending on ship type are observed
- Guidelines are suggested corresponding with three categories: container ships; oil tankers/bulk carriers; and LNG carriers
- Changes in outer water depth, or trench depth, of dredged channels substantially affect ship sinkage
- Blockage effects on the ships are found to be significant in canals

6 Acknowledgements

The authors would like to acknowledge:

- Dr. Evert Lataire and Prof. Marc Vantorre from Ghent University, and Dr. Guillaume Delefortrie from Flanders Hydraulics Research, for providing hull information for the FHR Ships D, F, and G
- Dr. Klemens Uliczka from BAW Hamburg, for providing hull information for the JUMBO and MEGA-JUMBO ships
- Dr. Suak Ho Van from KRISO, for providing hull information for the KLNG ship

7 References

- Beck, R.F., Newman, J.N. and Tuck, E.O. (1975): "Hydrodynamic forces on ships in dredged channels", *Journal of Ship Research*, 19(3), p.166-171.
- El Moctar, O., Shigunov, V. and Zorn, T. (2012): "Duisburg Test Case: Post-panamax container ship for benchmarking", *Ship Technology Research Schiffstechnik*, 59(3), p.50-64.
- Gourlay, T.P. (1999): "The effect of squat on steady nonlinear hydraulic flow past a ship in a channel", *Ship Technology Research Schiffstechnik*, 46(4), p.217-222.
- Gourlay, T.P. (2006): "Flow beneath a ship at small under keel clearance", *Journal of Ship Research*, 50(3), p.250-258.
- Gourlay, T.P. (2008a): "Dynamic draught of container ships in shallow water", *International Journal of Maritime Engineering*, 150(A4), p.43-56.
- Gourlay, T.P. (2008b): "Validation of KeelClear software in Torres Strait", *CMST Report 2008-05*.
- Gourlay, T.P. (2013): "Ship squat in non-uniform water depth", *In: Proceedings of the Coasts & Ports 2013 Conference*, Manly, Australia.
- Gourlay, T.P. (2014): "ShallowFlow: a program to model ship hydrodynamics in shallow water", *In: Proceedings of the ASME 33rd International Conference on Ocean, Offshore and Arctic Engineering, OMAE 2014*, San Francisco, California, USA.
- Gourlay, T.P., Ha, J.H., Mucha, P. and Uliczka, K. (2015a): "Sinkage and trim of modern container ships in shallow water", *In: Proceedings of the Coasts & Ports 2015 Conference*, Auckland, New Zealand.
- Gourlay, T.P. and Klaka, K. (2007): "Full-scale measurements of containership sinkage, trim and roll", *Australian Naval Architect*, 11(2), p.30-36.
- Gourlay, T.P., Lataire, E. and Delefortrie, G. (2016): "Application of potential flow theory to ship squat in different canal widths", *In: Proceedings of the 4th International Conference on Ship Manoeuvring in Shallow and Confined Water, MASHCON 2016*, Hamburg, Germany.
- Gourlay, T.P., von Graefe, A., Shigunov, V. and Lataire, E. (2015b): "Comparison of AQWA, GL RANKINE, MOSES, OCTOPUS, PDSTRIP and WAMIT with model test results for cargo ship wave-induced motions in shallow water", *In: Proceedings of the ASME 34th International Conference on Ocean, Offshore and Arctic Engineering, OMAE 2015*, St. John's, Newfoundland, Canada.
- Graff, W., Kracht, A. and Weinblum, G. (1964): "Some extensions of D. W. Taylor's standard series", *Transactions of the Society of Naval Architects and Marine Engineers*, 72, p.374-401.
- Ha, J.H., Gourlay, T.P. and Nadarajah, N. (2016): "Measured ship motions in Port of Geraldton approach channel", *In: Proceedings of the 4th International Conference on Ship Manoeuvring in Shallow and Confined Water, MASHCON 2016*, Hamburg, Germany.
- Hooft, J.P. (1974): "The behaviour of a ship in head waves at restricted water depth", *International Shipbuilding Progress*, 244(21), 367.
- Huuska, O. (1976): "On the evaluation of underkeel clearances in Finnish waterways", Helsinki University of Technology, Ship Hydrodynamics Laboratory, Otaniemi, *Report No. 9*.
- ICORELS (International Commission for the Reception of Large Ships) (1980): "Report of Working Group IV", *PIANC Bulletin No. 35, Supplement*.
- Jachowski, J. (2008): "Assessment of ship squat in shallow water using CFD", *Archives of Civil and Mechanical Engineering*, 8(1), p.27-36.
- Larsson, L., Stern, F. and Bertram, V. (2003): "Benchmarking of computational fluid dynamics for ship flows: The Gothenburg 2000 Workshop", *Journal of Ship Research*, 47(1), p.63-81.
- Lee, S.J., Koh, M.S. and Lee, C.M. (2003): "PIV velocity field measurements of flow around a KRISO 3600TEU container ship model", *Journal of Marine Science and Technology*, 8(2), p.76-87.

- Millward, A. (1992): "A comparison of the theoretical and empirical prediction of squat in shallow water", *International Shipbuilding Progress*, 39(417), p.69-78.
- Mucha, P., el Moctar, O. and Böttner, U.C. (2014): "Technical note: PreSquat - Workshop on numerical prediction of ship squat in restricted waters", *Ship Technology Research Schiffstechnik*, 61(3), p.162-165.
- Nautical Institute (2015): "Navigation Accidents and their Causes", *The Nautical Institute Publications*.
- NMRI (2015): Tokyo 2015, "A Workshop on CFD in Ship Hydrodynamics", [Online], Available: <http://www.t2015.nmri.go.jp>
- PIANC (2014): "Harbour Approach Channels Design Guidelines", *PIANC Report No. 121*.
- Tuck, E.O. (1966): "Shallow water flows past slender bodies", *Journal of Fluid Mechanics*, 26, p.81-95.
- Tuck, E.O. (1967): "Sinkage and trim in shallow water of finite width", *Schiffstechnik*, 14, p.92-94.
- Uliczka, K., Kondziella, B. and Flügge, G. (2004): "Dynamisches fahrverhalten sehr großer containerschiffe in seitlich begrenztem extremen Flachwasser", *HANSA*, 141.
- Van, S.H., Kim, W.J., Yoon, H.S., Lee, Y.Y. and Park, I.R. (2006): "Flow measurement around a model ship with propeller and rudder", *Experiments in Fluids*, 40(4), p.533-545.
- Van, S.H., Kim, W.J., Yim, D.H., Kim, G.T., Lee, C.J. and Eom, J.Y. (1998): "Flow measurement around a 300K VLCC model", In: *Proceedings of the Annual Spring Meeting, The Society of Naval Architects of Korea (SNAK)*, Ulsan, Korea, p.185-188.
- Van, S.H., Yoon, H.S., Lee, Y.Y., Park, I.R., Lee, C.J. and Kim, W.J. (2003): "Measurement of flow around KRISO 138K LNG carrier model", *Journal of the Society of Naval Architects of Korea*, 40(2), p.1-10.
- Vantorre, M. (2003): "Review of practical methods for assessing shallow and restricted water effects", In: *International Conference on Marine Simulation and Ship Manoeuvrability, MARSIM 2003*, Kanazawa, Japan, WS-4-1-WS-4-11.
- Vantorre, M. and Journée, J.M.J. (2003): "Validation of the strip theory code SEAWAY by model tests in very shallow water", In: *Numerical Modelling Colloquium*, Flanders Hydraulics Research, Antwerp, Belgium, DUT-SHL Report Nr. 1373-E.
- von Graefe, A. (2014): "A Rankine source method for ship-ship interaction and shallow water problems", *University of Duisburg-Essen, Ph.D. Thesis*.
- Yokoo, K. (1966): "Systematic series model tests in Japan concerning the propulsive performance of full ship forms", *Japan Shipbuilding and Marine Engineering*, 1(2), p.13-22.

ABSTRACT

In this paper, we develop sinkage coefficients for ships in shallow open water, or harbour approach channels with minimal transverse restriction. These sinkage coefficients may be used for under-keel clearance management by ports, pilots, and deck officers. The coefficients are calculated using slender-body shallow-water theory applied to 12 published hull forms. Results are condensed into sinkage coefficient ranges for container ships, oil tankers, bulk carriers, and membrane LNG carriers. Limitations on use of the coefficients are suggested, based on ship and navigation channel dimensions. Examples are given for container ships, bulk carriers, and LNG carriers in Australian ports.

RESUME

Dans cet article, nous développons les coefficients d'enfoncement en eaux peu profondes ouvertes, ou dans les chenaux d'approches avec des restrictions transversales minimales. Ces coefficients peuvent être utilisés pour la gestion du clair sous quille par les ports, les pilotes et les officiers de pont. Les coefficients sont calculés en utilisant la théorie des corps minces en eaux peu profondes appliquée aux 12 formes de coque publiées. Les résultats sont inclus dans des gammes de coefficients d'enfoncement pour les porte-conteneurs, les pétroliers, les vraquiers, les méthaniers à membrane. Les limites d'utilisation de ces coefficients sont suggérées sur la base des dimensions des navires et des chenaux. Des exemples sont donnés pour les porte-conteneurs, les vraquiers, les méthaniers dans les ports australiens.

ZUSAMMENFASSUNG

In diesem Artikel werden Einsinkungs-Koeffizienten für Schiffe in flachem, offenem Wasser oder in Hafenzufahrten mit minimaler Querbeschränkung beschrieben. Diese Einsinkungs-Koeffizienten können für das Management der Kieľfreiheit durch Häfen, Piloten und Deckoffiziere verwendet werden. Die Koeffizienten werden mit Hilfe von schmalen Körpern und der Flachwassertheorie für 12 bekannte Rumpfformen berechnet. Die Ergebnisse werden in Einsinkungs-Koeffizienten-Kategorien für Containerschiffe, Öltanker, Massengutfrachter und Membran-LNG-Frachter zusammengefasst. Auf der Basis der Abmessungen der Schiffe und der Fahrrinne werden Einschränkungen für die Anwendung der Koeffizienten vorgeschlagen. Beispiele für Containerschiffe, Massengutfrachter und LNG-Frachter in australischen Häfen werden gegeben.

RESUMEN

En este trabajo se desarrolla el cálculo de coeficientes de hundimiento a popa para buques operando en aguas someras abiertas o en canales de aproximación a puertos, con mínimas restricciones en el sentido transversal. Estos coeficientes de hundimiento se pueden utilizar para la gestión de resguardos bajo quilla por parte del personal de los puertos, prácticos o personal del puente. Los coeficientes se han calculado como un sólido esbelto situado en aguas someras, utilizando 12 referencias disponibles para distintos tipos de cascos. Los resultados se condensan en rangos de variación de los coeficientes dependiendo de si se trata de portacontenedores, buques tanque, graneleros o gaseros tipo membrana. Se sugieren limitaciones para el uso de estos coeficientes, derivados del tipo de buque y de las dimensiones del canal de navegación. Se muestran ejemplos de uso para portacontenedores, graneleros y gaseros en puertos australianos.
